

Package: nesstarR (via r-universe)

October 17, 2026

Type Package

Title Read and Export 'Nesstar' Binary Files

Version 0.1.0

Description Reads '.Nesstar' binary files into data frames. '.Nesstar' is the file format of 'Nesstar Publisher', survey documentation software from the International Household Survey Network <<https://www.ihsn.org/node/557>>. Statistical agencies, for example the Ministry of Statistics and Programme Implementation ('MoSPI', India), publish survey microdata in this format.

License MIT + file LICENSE

URL <https://nesstarr.saketlab.org>, <https://github.com/saketkc/nesstarR>

BugReports <https://github.com/saketkc/nesstarR/issues>

Encoding UTF-8

Language en-US

Depends R (>= 4.1.0)

Imports tools, utils

Suggests haven, knitr, rmarkdown, testthat (>= 3.0.0)

Config/testthat/edition 3

Config/Needs/website pkgdown, archive, saketkc/mospiR

VignetteBuilder knitr

NeedsCompilation yes

Config/roxygen2/version 8.1.0

Repository <https://saketlab.r-universe.dev>

Date/Publication 2026-10-17 07:25:31 UTC

RemoteUrl <https://github.com/saketkc/nesstarR>

RemoteRef HEAD

RemoteSha b29f75c170dd1ffae3cef9d4889864f39807c825

Contents

nesstar_compare	2
nesstar_datasets	3
nesstar_export	3
nesstar_metadata	4
nesstar_parse	5
nesstar_read_dataset	6
nesstar_variables	6
Index	8

nesstar_compare	<i>Compare a dataset with a reference data frame</i>
-----------------	--

Description

Compares one dataset of a Nesstar file with the same data from a different source, for example a Stata or SPSS export. Use this function to make sure that nesstarR decodes a file correctly.

Usage

```
nesstar_compare(x, dataset_number, reference)
```

Arguments

- x A nesstar_binary object from [nesstar_parse](#).
- dataset_number Integer dataset number.
- reference A data frame with the same rows, in the same order.

Details

The function matches the columns by name. Before the match, it changes each group of characters that are not letters or digits to `_`, removes `_` from the start and the end, and changes the names to upper case. Thus, `Sr1._No.` and `Sr1_No` are the same column.

If all values in the two columns are numbers, the function compares the numbers. Thus, `"010"` and `10` are equal. Otherwise, it compares the values as text, without leading and trailing spaces. Empty strings and NA are equal.

Remove value labels from reference before the comparison, for example with `haven::zap_labels()`.

Value

A data frame with one row for each column name and these columns:

- column The column name after the change.
- in_nesstar, in_reference TRUE if the column is in the source.
- different_values The number of rows with different values. NA if the column is in only one source.

Examples

```
path <- system.file("extdata", "example.Nesstar", package = "nesstarR")
x <- nesstar_parse(path)
reference <- nesstar_read_dataset(x, dataset_number = 1)
reference$AGE[1] <- 26
nesstar_compare(x, dataset_number = 1, reference = reference)
```

nesstar_datasets	<i>List the datasets in a Nesstar file</i>
------------------	--

Description

List the datasets in a Nesstar file

Usage

```
nesstar_datasets(x)
```

Arguments

x A nesstar_binary object from [nesstar_parse](#).

Value

A data frame with columns dataset_number, row_count, variable_count.

Examples

```
path <- system.file("extdata", "example.Nesstar", package = "nesstarR")
x <- nesstar_parse(path)
nesstar_datasets(x)
```

nesstar_export	<i>Export datasets to CSV files</i>
----------------	-------------------------------------

Description

Writes each dataset to a different CSV file. The file name contains the name of the Nesstar file and the dataset number.

Usage

```
nesstar_export(
  x,
  output_dir,
  datasets = NULL,
  compress = TRUE,
  chunk_size = 50000L
)
```

Arguments

x	A nesstar_binary object.
output_dir	Directory for the output files. If the directory does not exist, the function makes it.
datasets	Integer vector of the dataset numbers to export. If NULL (the default), the function exports all datasets.
compress	Logical. If TRUE (the default), the function writes gzip files (.csv.gz).
chunk_size	Number of rows to read at a time. A smaller value decreases the memory use.

Value

Invisibly, a character vector of output file paths.

Examples

```
path <- system.file("extdata", "example.Nesstar", package = "nesstarR")
x <- nesstar_parse(path)
out <- nesstar_export(x, output_dir = tempdir())
read.csv(out[1])
```

nesstar_metadata	<i>Read the XML metadata of a Nesstar file</i>
------------------	--

Description

Decodes the Huffman-coded XML blocks in the file. The XML blocks contain the dataset file names, the variable labels and the category labels.

Usage

```
nesstar_metadata(x)
```

Arguments

x	A nesstar_binary object from nesstar_parse .
---	--

Details

Some older NSS files use different record IDs. For these files, the function cannot decode the metadata. It gives a warning and returns NULL.

Value

A named list:

datasets A list with one element for each dataset. Each element contains dataset_number, file_name and variables. variables is a list with one list for each variable. Each variable list contains name, label and categories.

If the function cannot decode the metadata, it returns NULL.

Examples

```
path <- system.file("extdata", "example.Nesstar", package = "nesstarR")
x <- nesstar_parse(path)
meta <- nesstar_metadata(x)
meta$datasets[[1]]$variables[[1]]$label
```

nesstar_parse

Parse a Nesstar file

Description

Decodes the resource index, the dataset descriptors and the variable directories. Does not decode row data.

Usage

```
nesstar_parse(path)
```

Arguments

path	Path to a .Nesstar file.
------	--------------------------

Details

The function does not keep the file in memory. The other functions read only the bytes that they need from the file. Thus, the memory use does not increase with the file size. Do not move or change the file while you use the result.

Value

A nesstar_binary list (S3 class).

Examples

```
path <- system.file("extdata", "example.Nesstar", package = "nesstarR")
x <- nesstar_parse(path)
x
```

`nesstar_read_dataset` *Read one dataset into an R data frame*

Description

Numeric columns (mode 5) become numeric. String columns (mode 1) become character. Missing values become NA.

Usage

```
nesstar_read_dataset(x, dataset_number, columns = NULL)
```

Arguments

`x` A `nesstar_binary` object.

`dataset_number` Integer dataset number.

`columns` Character vector of the column names to read. If NULL (the default), the function reads all columns.

Value

A `data.frame`.

Examples

```
path <- system.file("extdata", "example.Nesstar", package = "nesstarR")
x <- nesstar_parse(path)
nesstar_read_dataset(x, dataset_number = 1)
nesstar_read_dataset(x, dataset_number = 1, columns = c("AGE", "NAME"))
```

`nesstar_variables` *List variables in one dataset*

Description

List variables in one dataset

Usage

```
nesstar_variables(x, dataset_number)
```

Arguments

`x` A `nesstar_binary` object.

`dataset_number` Integer dataset number (as shown by [nesstar_datasets](#)).

Value

A data frame with one row for each variable. The columns give the storage format of the variable.

Examples

```
path <- system.file("extdata", "example.Nesstar", package = "nesstarR")
x <- nesstar_parse(path)
nesstar_variables(x, dataset_number = 1)
```

Index

nesstar_compare, [2](#)
nesstar_datasets, [3](#), [6](#)
nesstar_export, [3](#)
nesstar_metadata, [4](#)
nesstar_parse, [2](#)–[4](#), [5](#)
nesstar_read_dataset, [6](#)
nesstar_variables, [6](#)